

Yale

**Narrow Aisle
3,000-5,000 lb.**

Yale® Narrow Aisle Lift Trucks have the ergonomic comfort and the specifications you need. Yale designs and builds narrow aisle trucks that are industry and application specific. Drive motors are application proven for efficiency, performance, and reliability. Yale Hi-Vis masts incorporate innovative engineering for unsurpassed visibility and solid construction.



**NR/NDR030-040DA
NR/NDR030-045EA**



OS030EC



OS/SS030BE



NTA030-035SB

GENERAL	Type	Single Reach	Double Reach	High Lift Single Reach	High Lift Double Reach	Order Selector	Order Selector	Straddle Selector	Very Narrow	
	Yale model designation		NR035-040DA	NDR030DA	NR035-045EA	NDR030-035EA	OS030EC	OS030BE	SS030BE	NTA030-035SB
Capacity range	lbs.	3500-4000	3000	3500-4500	3000-3500	3000	3000	3000	3000-3500	
Power Steering		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	
Yale Hi-Vis mast		Standard	Standard	Standard	Standard	Standard	Standard	Standard	—	
DIMENSIONS	Length to face of forks	in.	52.12-54.12	58.02-60.02	52.12-62.59	58.02-68.50	72.03-73.03	74.0-75.3	98.5	135.6-159.0
	Chassis width	in.	42.8	42.8	42.8	42.8	40	40	40	48-69
	Height	in.	87-119	87-119	87-179	87-179	89-105	89.4-119	89.4-131	118.1
	Right angle turn	in.	85-96	90-101	85-102	90-105	—	—	—	—
	Mast maximum fork height	Simplex	in.	—	—	—	165	—	—	525.2
		Triplex	in.	272	272	422	422	240	276	300
Quadplex		in.	—	—	—	—	—	—	668	
DRIVE	Drive control		AC	AC	AC	AC	SEM Transistor	SEM Transistor	SEM Transistor	AC
	Voltage		24-36	24-36	36	36	24	24-36	24-36	48-72
	Maximum travel speed—mph—empty		6.7	6.7	7.4-8.0	7.4-8.0	6.0	6.0-6.5	5.3-7.5	6.5

General notes: Truck performance may be affected by the condition of the vehicle, how it is equipped and the application. Specifications represent a general guide for standard Yale models and are subject to change without notice. Products listed in this full line catalog are subject to change without notice. Visit www.yale.com for the most up-to-date product offering.